## Reducing the effect of light shift on a pulsed CPT-based clock

<u>M. Petersen<sup>1</sup></u>, M. Abdel Hafiz<sup>4</sup>, G. Coget<sup>1</sup>, C. E. Calosso<sup>2</sup>, S. Gu\_erandel<sup>3</sup>,

E. de Clercq<sup>3</sup>, R. Boudot<sup>1</sup>

<sup>1)</sup>FEMTO-ST, CNRS, UBFC, 26 rue de l'\_epitaphe 25030 Besançon, France. <sup>2)</sup>INRIM, Strada delle Cacce 91, 10135 Torino, Italy. <sup>3)</sup>LNE-SYRTE, Observatoire de Paris, Université PSL, CNRS, Sorbonne Université, 61 avenue de l'Observatoire 75014 Paris, France. <sup>4)</sup>PTB, Bundesallee 100, D-38116 Braunschweig, Germany.

Vapor cell atomic clocks are widely appreciated for their excellent short-term fractional frequency stability and their compactness. However, they are known to suffer on medium and long time scales from significant frequency instabilities, generally attributed to light-induced frequency shift effects. We will show the inprogress improvement of a high-performance Cs cell CPT-based atomic clock. There will be a strong emphasis on the first realization and result of the auto-balanced Ramsey interrogation protocol on a CPT-based Cs cell clock showing promising results for significantly reducing the effect of light shift on the frequency. The Allan deviation of the clock frequency has been improved to  $2 \times 10^{-13} \tau^{-1/2}$  for 10000 s of averaging time reaching  $2 \times 10^{-15}$  at 10000 s.